

312 G

Gauge with glycerine bath

Desbordes

Technical Data Sheet



Description

The Gauge with glycerine bath 312 G protects from vibrations.



312 G

Gauge with glycerine bath DESBORDES

PFA in bar	Ref.	Designation
1	149B7678	Gauge
4	149B7682	Gauge
6	149B7683	Gauge
10	149B7679	Gauge
16	149B7680	Gauge
25	149B7681	Gauge

Technical features

Operating temperature	-20 °C at +60 °C
Casing	Stainless steel with axial connection
Connection	Male thread 1/4", vertical
Face	Diameter 60 mm
Mediums	Water, air, neutral gas

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



A WATTS Brand

Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France

Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42

contact@wattswater.com • www.socla.com

ISO 9001 version 2015 / ISO 18001